

installed in a manner to insure unobstructed visibility of the beacons from aircraft at any normal angle of approach, there shall be installed two such beacons at each level. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

10.1 On levels at approximately eight-elevenths, six-elevenths, four-elevenths and two elevenths of the overall height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event these beacons cannot be installed in a manner to insure unobstructed visibility of the beacons from aircraft at any normal angle of approach, there shall be installed two such beacons at each level. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

10.2 On levels at approximately five-sixths, two-thirds, one-half, one-third and one-sixth of the over-all height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event these beacons cannot be installed in a manner to insure unobstructed visibility of the beacons from aircraft at any normal angle of approach there shall be installed two such beacons at each level. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

10.3 On levels at approximately ten-thirteenths, eight-thirteenths, six thirteenths, four-thirteenths and two-thirteenths of the over-all height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event these beacons cannot be installed in a manner to insure unobstructed visibility of the beacons from aircraft at any normal angle of approach, there shall be installed two such beacons at each level. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

10.4 On levels at approximately six-sevenths, five-sevenths, four-sevenths, three-sevenths two-sevenths and one-seventh of the over-all height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event these beacons cannot be installed in a manner to insure unobstructed visibility of the beacons from aircraft at any normal angle of approach, there shall

be installed two such beacons at each level. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

(SIDE LIGHTS)

11 At the approximate mid point of the over-all height of the tower there shall be installed at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes. Each light shall be mounted so as to insure unobstructed visibility of at least one light at each level from aircraft at any normal angle of approach.

12 On levels at approximately two-thirds and one-third of the over-all height of the tower, there shall be installed at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes. Each light shall be mounted so as to insure unobstructed visibility of at least one light at each level from aircraft at any normal angle of approach.

13 On levels at approximately three-fourths and one-fourth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in aviation red obstruction light globe shall be installed on each outside corner of the structure.

14 On levels at approximately four-fifths, three-fifths and one-fifth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

15 On levels at approximately five-sixths, one-half, and one-sixth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of structure.

16 On levels at approximately six-sevenths, five-sevenths, three-sevenths and one-seventh of the over-all height of the tower at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

17 On levels at approximately seven-eighths, five-eighths, three-eighths and one-eighth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

18 On levels at approximately eight-ninths, seven-ninths, five-ninths, one-third and one-ninth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

19 On levels at approximately nine-tenths, seven-tenths, one-half, three-tenths and one-tenth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

19.1 On levels at approximately ten-elevenths, nine-elevenths, seven-elevenths, five-elevenths, three-elevenths and one-eleventh of the over-all height of the tower at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

19.2 On levels at approximately eleven-twelfths, three-fourths, seven-twelfths, five-twelfths, one-fourth and one-twelfth of the over-all height of the tower at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

19.3 On levels at approximately twelve-thirteenths, eleven-thirteenths, nine-thirteenths, seven-thirteenths, five-thirteenths, three-thirteenths and one-thirteenth of the over-all height of the tower at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

19.4 On levels at approximately thirteen-fourteenths, eleven-fourteenths, nine-fourteenths, one-half, five-fourteenths three-fourteenths and one-fourteenth of the over-all height of the tower at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

20 All lighting shall be exhibited from sunset to sunrise unless otherwise specified.

21 All lights shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

22 During construction of an antenna structure, for which obstruction lighting is required, at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes, shall be installed at the uppermost point of the structure. In addition, as the height of the structure exceeds each level at which permanent obstruction lights will be required, two similar lights shall be displayed nightly from sunset to sunrise until the permanent obstruction lights have been installed and placed in operation, and shall be positioned so as to insure unobstructed visibility of at least one of the lights at any normal angle of approach. In lieu of the above temporary warning lights, the permanent obstruction lighting fixtures may be installed and operated at each required level as each such level is exceeded in height during construction.