



United States of America
FEDERAL COMMUNICATIONS COMMISSION
FM BROADCAST STATION LICENSE
AUXILIARY ANTENNA

Official Mailing Address:

THE PRES. & TRUSTEES OF MIAMI UNIV.
 WILLIAMS HALL
 OXFORD, OH 45056

Authorizing Official:

for James A. Doak

Arthur E. Doak
 Supervisory Engineer
 Audio Services Division
 Mass Media Bureau

Grant Date: **MAR 28 1996**

Call Sign: WMUB

This license expires 3:00 a.m.
 local time, October 01, 1996

License File No.: BMLED-951121KA

This license modifies License No.: BLED-821201AG
 Dated: 04/21/83

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Name of Licensee:

THE PRESIDENT & TRUSTEES OF THE MIAMI UNIVERSITY



Station Location:

OH-OXFORD

Frequency (MHz): 88.5

Channel: 203

Class: B

Hours of Operation: Unlimited -- For auxiliary purposes only

Main Studio Address:

OH-WILLIAMS HALL, MIAMI UNIVERSITY, OXFORD

Transmitter location (address or description):

OH-1.71 KILOMETERS SOUTHEAST OF COLLEGE CORNER

Remote Control Point Address:

OH - WILLIAMS HALL, CORNER OF SPRING & OAK STREETS, OXFORD

Transmitter: Type Accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power: 3.7 kW

Antenna type: (directional or non-directional): Directional

Description: JAMPRO/CETEC JSLP-3RDA, 3 SECTIONS

Antenna Coordinates: North Latitude :	39	33	26
West Longitude :	84	47	35

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the Horizontal Plane (kW).....:	17.0	17.0
Height of radiation center above ground (Meters).....:	131	131
Height of radiation center above mean sea level (Meters).....:	436	436
Height of radiation center above average terrain (Meters).....:	142	142

Overall height of antenna structure above ground (including obstruction lighting if any): 149 Meters

Obstruction marking and lighting specifications for antenna structure:

It is to be expressly understood that the issuance of these specifications

is in no way to be considered as precluding additional or modified marking or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

PARAGRAPH 01.0, FCC FORM 715 (OCTOBER 1985):

Antenna structures shall be painted throughout their height with alternate bands of aviation surface orange and white, terminating with aviation surface orange bands at both top and bottom. The width of the bands shall be equal and approximately one-seventh the height of the structure, provided however, that the bands shall not be more than 100 feet nor less than 1 and 1/2 feet in width. All towers shall be cleaned and repainted as often as necessary to maintain good visibility.

PARAGRAPH 03.0, FCC FORM 715 (APRIL 1985):

There shall be installed at the top of the structure one 300 m/m electric code beacon equipped with two 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. Where a rod or other construction of not more than 20 feet in height and incapable of supporting this beacon is mounted on top of the structure and it is determined that this additional construction does not permit unobstructed visibility of the code beacon from aircraft at any normal angle of approach, there shall be installed two such beacons positioned so as to insure unobstructed visibility of at least one of the beacons from aircraft at any normal angle of approach. The beacons shall be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.

PARAGRAPH 04.0, FCC FORM 715 (APRIL 1985):

At approximately one-half of the overall height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event this beacon cannot be installed in a manner to insure unobstructed visibility of it from aircraft at any normal angle of approach, there shall be installed two such beacons. Each beacon shall be mounted on the outside of the tower at the prescribed height.

PARAGRAPH 13.0, FCC FORM 715 (APRIL 1985):

On levels at approximately three-fourths and one-fourth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

PARAGRAPH 21.0, FCC FORM 715 (APRIL 1985):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

