United States of America FEDERAL COMMUNICATIONS COMMISSION

FM BROADCAST STATION LICENSE

53 Subject to the provisions of the Communications Act of 1934, as amended, treaties, and Commission Rules, and further subject to conditions set forth in this license to the UICENSEE

PORTER BROADCASTING - INC.

is hereby authorized to use and operate the radio transmitting apparatus hereinafter described for the purpose of broadcasting for the term ending 3 a.m. Local Time: April 1, 1, 1978.

The licensee shall use and operate said apparatus only in necordance with the following terms:

1. Frequency (MHz) 105.7

2. Transmitter output power . . . : 20 kilowatts

3. Effective radiated power : 5D kilowatts {H&V}

4. Antenna height above

average terrain (fee:): 500 feet {H&V}

6. Station location Batha Maine

7. Main studio location Berry s Mill Road West

Bath, Maine

8. Remote Control point: Berry s Mill Road West

Bath, Maine

9. Antenna & supporting Structure: North Latitude: 44 9 04

West Longitude: 67 9 55 28

HARRIS, FMH-5AE, 5 sections H&V, side-mounted near the top of a uniform, cross-section, guyed. steel tower. Overall height above ground: 360 feet

10. Transmitter location: 3.3 miles NE of Bowdoin Center on Arnold Hwy. {US 201}, Bowdoin, Maine

11. Transmitter(s) GATES, FM-20H3

12. Obstruction markings specifications in accordance with the following paragraphs of FCC Corm 715: 13 37 125 21

13. Conditions:

The Commission reserves the right duting said license period of terminating this license or making effective any changes or modification of this figense which may be necessary to comply with any decision of the Commission rendeted as a result of any bearing held under the rules of the Commission prior to the commencement of this license period or any decision rendered as a result of any such hearing which has been design nated but not held, prior to the commencement of this license period.

This license is Issued on the licensee's representation that the statements contained in licensee's application are true and that the uncertakings therein contained so far as they are consistent berewith, will be entired out in good faith. The livensee shall, during the term of this license, render such broadcasting service as will serve public interest, convenience, or necessity to the full extent of the privileges berein conferred.

This license shall not vest in the licensee any right to operate the station nor any tight in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the livense nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use at control by the Government of the United States conferred by section 606 of the Communications Act of 1934.

This license consists of this page and paken

August 10, 1977

FEDERAL COMMUNICATIONS COMMISSION



kim Dated:

LICENSE RENEWAL AUTHORIZATION

THIS IS TO NOTIFY YOU THAT YOUR APPLICATION FOR RENEWAL OF LICENSE, BRH-20131121BBI, WAS GRANTED ON 03/24/2014 FOR A TERM EXPIRING ON 04/01/2022.

THIS IS YOUR LICENSE RENEWAL AUTHORIZATION FOR STATION WBCI.

FACILITY ID: 33288

LOCATION: BATH, ME

THIS CARD MUST BE POSTED WITH THE STATION'S LICENSE CERTIFICATE AND ANY SUBSEQUENT MODIFICATIONS.

BLOUNT COMMUNICATIONS, INC. 122 MAIN ST TOPSHAM, ME 04086

REFERENCE COPY

This is not an official FCC license. It is a record of public information contained in the FCC's licensing database on the date that this reference copy was generated. In cases where FCC rules require the presentation, posting, or display of an FCC license, this document may not be used in place of an official FCC license.



UNITED STATES OF AMERICA FEDERAL COMMUNICATIONS COMMISSION ANTENNA STRUCTURE REGISTRATION



OWNER: BLOUNT COMMUNICATIONS INC

FCC Registration Number (FRN):	0003760378			
ATTN: BILL BLOUNT BLOUNT COMMUNICAT 19 LUTHER AVE WARWICK, RI 02886			Antenna Structure Registration Number	1046222
			Issue Date	08-19-2010
Location of Antenna Structure ADAMS RD			Ground Elevation (AMSL)	115.5 meters
BOWJOIN, ME			Overall Height Above Groun	nd (AGL) 114.9 meters
Latitude 44-04-09.2 N	Longitude 069-55-27.1 W	NAD83	Overall Height Above Mean	Sea Level (AMSL) 230.4 meters
Painting and Lighting Requirement FCC Paragraphs 1, 3, 12, 21 Conditions:	nts:			

This registration is effective upon completion of the described antenna structure and notification to the Commission. YOU MUST NOTIFY THE COMMISSION WITHIN 24 HOURS OF COMPLETION OF CONSTRUCTION OR CANCELLATION OF YOUR PROJECT, please file FCC Form 854. To file electronically, connect to the antenna structure registration system by pointing your web browser to http://wireless.fcc.gov/antenna. Electronic filing is recommended. You may also file manually by submitting a paper copy of FCC Form 854. Use purpose code "NT" for notification of completion of construction, use purpose code "CA" to cancel your registration.


The Antenna Structure Registration is not an authorization to construct radio facilities or transmit radio signals. It is necessary that all radio equipment on this structure be covered by a valid FCC license or construction permit.

You must immediately provide a copy of this Registration to all tenant licensees and permittees sited on the structure described on this Registration (although not required, you may want to use Certified Mail to obtain proof of receipt), and *display* your Registration Number at the site. See reverse for important information about the Commission's Antenna Structure Registration rules.

You must comply with all applicable FCC obstruction marking and lighting requirements, as set forth in Part 17 of the Commission's Rules (47 C.F.R. Part 17). These rules include, but are not limited to:

- Posting the Registration Number: The Antenna Structure Registration Number must be displayed in a conspicuous place so that it is readily visible near the base of the antenna structure. Materials used to display the Registration Number must be weather-resistant and of sufficient size to be easily seen at the base of the antenna structure. Exceptions exist for certain historic structures. See 47 C.F.R. 17.4(g)-(h).
- Inspecting lights and equipment: The obstruction lighting must be observed at least every 24 hours in order to detect any outages or malfunctions. Lighting equipment, indicators, and associated devices must be inspected at least once every three months.
- Reporting outages and malfunctions: When any top steady-burning light or a flashing light (in any position) burns out or malfunctions, the outage must be reported to the nearest FAA Flight Service Station, unless corrected within 30 minutes. The FAA must again be notified when the light is restored. The owner must also maintain a log of these outages and malfunctions.
- Maintaining assigned painting: The antenna structure must be repainted as often as necessary to maintain good visibility.
- Complying with environmental rules: If you certified that grant of this registration would not have a significant environmental impact, you must nevertheless maintain all pertinent records and be ready to provide documentation supporting this certification and compliance with the rules, in the event that such information is requested by the Commission pursuant to 47 C.F.R. 1.1307(d).
- Updating information: The owner must notify the FCC of proposed modifications to this structure; of any change in ownership; or, within 30 days of dismantlement of the structure.

Copies of the Code of Federal Regulations (which contain the FCC's antenna structure registration rules, 47 C.F.R Part 17) are available from the Government Printing Office (GPO). To purchase CFR volumes, call (202) 512-1800. For GPO Customer Service, call (202) 512-1803. For additional FCC information, consult the Antenna Homepage on the internet at http://wireless.fcc.gov/antenna or call (877) 480-3201 (TTX 717-338-2824).



Registration #: 1046222 Issue Date: 08-19-2010

. 5 ⁵⁵

OBSTRUCTION MARKING AND LIGHTING SPECIFICATIONS FOR ANTENNA STRUCTURES

It is to be expressly understood that the issuance of the below specifications is in no way to be considered as precluding additional or modified markings or lighting as may hereafter be required under the provisions of Section 303(q) of the Communications Act of 1934, as amended.

- 1 Antenna structures shall be painted throughout their height with alternate bands of aviation surface orange and white, terminating with aviation surface orange bands at both top and bottom. The width of the bands shall be equal and approximately one-seventh the height of the structure, provided however, that the bands shall not be more than 30.48 meters (100 feet) nor less than 46 meters (11/2 feet) in width. All towers shall be cleaned or repainted as often as necessary to maintain good visibility.
- 3 There shall be installed at the top of the structure one 300 m/m electric code beacon equipped with two 620- or 700-watt lamps (PS-40, Code Beacon type), both lamps to burn simultaneously, and equipped with aviation red color filters. Where a rod or other construction of not more than 6.10 meters (20 feet) in height and incapable of supporting this beacon is mounted on top of the structure and it is determined that this additional construction does not permit unobstructed visibility of the code beacon from aircraft at any normal angle of approach, there shall be installed two such beacons positioned so as to insure unobstructed visibility of at least one of the beacons from aircraft at any normal angle of approach. The beacons shall be equipped with a flashing mechanism producing not more than 40 flashes per minute nor less than 12 flashes per minute with a period of darkness equal to approximately one-half of the luminous period.
- 12 On levels at approximately two-thirds and one-third of the overall height of the tower, there shall be installed at least two 116- or 125-watt lamps (A21/TS) enclosed in aviation red obstruction light globes. Each light shall be mounted so as to insure unobstructed visibility of at least one light at each level from aircraft at any normal angle of approach.
- 21 All lights shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.

